



| REV | DESCRIPTION | DATE | APP |
|------------------|-----------------|------------|-----|
| 0 | INITIAL RELEASE | 01/10/2019 | DD |
| REVISION HISTORY | | | |

| | | |
|--|-----------------------|------------------|
| EI SENSOR TECHNOLOGIES www.ei-sensor.com © COPYRIGHT | RTD ELEMENT | |
| | DRAWN BY: DAN DANKERT | |
| P/N ERTD1A501 | SCALE: NONE | LAYER: 0 OF 2 |
| | REV: 0 | DATE: 01/10/2019 |

RESISTANCE @ 0°C = 500 Ω ± 0.06%
 ACCURACY @ 0°C = ± 0.15°C
 DIN 43760 ACCURACY CLASS = "A"
 TCR = 3,850 ppm/°C
 DISSIPATION CONSTANT = 2 mW/°C NOMINAL (AIR @ 1m/SECOND)
 MAXIMUM APPLIED CURRENT = 1 mA
 THERMAL TIME CONSTANT = 15 SECONDS MAXIMUM (AIR @ 1m/SECOND)
 TEMPERATURE RATING = -50 TO +500°C

ROHS COMPLIANT

This PROPRIETARY document is the property of EI Sensor Technologies. It is confidential in nature, non-transferrable and issued with the understanding that it is not to be traced or copied without permission, and is returnable on demand.